

Specification and Description “Exhibit A”

STATIONAIR TC

Specification and Description

Dated January 2006

Beginning With Serial #T20608586

Manufacturer: Cessna Aircraft Company Model: T206H

Initial _____



Specification and Description “Exhibit A”

The Cessna Turbo Stationair

Introduction

This document is published for the purpose of providing general information for the evaluation of design, performance and equipment of the Cessna Turbo Stationair. Should more information be required, please contact:

Cessna Aircraft Company
Single Engine Piston Aircraft
2625 S. Hoover Rd.
Wichita, Kansas 67215
1-800-4-CESSNA
www.se.cessna.com

This document supersedes all previous Specification and Description documents and describes only the Turbo Stationair Model T206H, its powerplant and equipment. Also included are the warranties applicable to the Turbo Stationair Model T206H aircraft, the Textron Lycoming TIO-540-AJ1A engine, the McCauley propeller and the OEM installed Bendix/King and Garmin avionics. In the event of any conflict or discrepancy between this document and the basic purchase agreement, the basic purchase agreement language shall govern. Due to the time span between the date of this Specification and Description and the scheduled delivery date of the aircraft, Cessna reserves the right to revise the “Specification” whenever occasioned by product improvements, government regulations or other good cause.

Specification and Description

“Exhibit A”

General Description

All information herein applies to the Turbo Stationair (Model T206H).

The Turbo Stationair is an all-metal, six-place, high-wing, fixed gear, single-engine piston aircraft designed for general utility purposes. The Model T206H is certified to the requirements of U.S. FAA Federal Aviation Regulation Part 23 through amendment 23-6, including day, night, VFR and IFR.

Approximate Dimensions

Overall Height (max).....	9'3.5" (2.83 m)
Overall Length.....	28'3" (8.61 m)
Wing	
Span (overall).....	36' (10.97 m)
Area.....	174 sq ft (16.2 sq m)
Cabin	
Height (max).....	49.5" (1.26 m)
Length (firewall to aft baggage area).....	145" (3.68 m)
Width.....	44" (1.12 m)
Cabin Door	
Height (front).....	41" (1.04 m)
Height (rear).....	39" (1.00 m)
Width (top).....	32.5" (.83 m)
Width (bottom).....	37" (.94 m)
Cargo Doors	
Height (front).....	39.25" (1.00 m)
Height (rear).....	37.5" (.95 m)
Width (top).....	43" (1.09 m)
Width (bottom).....	40" (1.02 m)

Design Weights and Capacities

Maximum Ramp Weight.....	3,617 lbs (1,641 kg)
Maximum Takeoff Weight.....	3,600 lbs (1,633 kg)
Maximum Landing Weight.....	3,600 lbs (1,633 kg)
Standard Empty Weight.....	2,351 lbs (1066 kg)
Maximum Useful Load.....	1,266 lbs (574 kg)
Baggage Allowance.....	180 lbs (82 kg)
Fuel Capacity	
Total capacity.....	92 gal (348.2 L)
Total usable.....	87 gal (329.3 L)
Total capacity each tank.....	46 gal (174.1 L)
Total usable capacity each tank.....	43.5 gal (164.6 L)
Oil Capacity	
Sump.....	8 qts (7.5 L)
Total Capacity.....	9 qts (8.5 L)

Specification and Description

“Exhibit A”

Turbo Stationair Equipment List

The following list of equipment is included on the standard aircraft and it does not reflect optional equipment.

AVIONICS:

GDU-1040 Primary Flight Display (PFD)
GDU-1040 Multi-function Display (MFD)
GMA-1347 Digital Audio Panel w/Marker Beacon/Intercom
CI-102 Marker Beacon Antenna
GIA-63 NAV/COM/GPS w/GS #1
GIA-63 NAV/COM/GPS w/GS #2
CI-2480 VHF/GPS Antenna w/Internal Notch Filter #1
CI-2480 VHF/GPS Antenna w/Internal Notch Filter #2
CI-120 NAV Antenna
GTX-33 Transponder - Mode S w/TIS
CI-105 Transponder Antenna
GEA-71 Engine/Airframe Computer

- CHT/EGT Sensors - All Cylinders
- Fuel Flow Meter
- Manifold/Tachometer/Vacuum Sensors

GRS-77 AHRS
GDC-74 Air Data Computer w/OAT Probe
GMU-44 Magnetometer
KAP-140 Dual Axis Autopilot

- Altitude Preselect
- GPS Roll Steering
- KCM-100 Configuration Module
- KS-270C Pitch Axis Servo Actuator
- KS-271C Roll Axis Servo Actuator
- KS-272C Pitch Trim Servo Actuator

3000-11 Emergency Locator Transmitter
Emergency Locator Transmitter External Antenna
Emergency Locator Transmitter Remote Mounted Switch
WX-500 Stormscope
NY-163 Stormscope Antenna
Control Wheel Push-To-Talk Switch - Pilot/Copilot
Mic & Phone Jacks -
Pilot/Copilot/Passengers
Auxiliary Stereo Input Jack
Blind Turn Coordinator for KAP-140
Avionics Circuit Breaker Panel
Control Wheel Push-To-Talk Switch - Pilot/Copilot
Mic & Phone Jacks - Pilot/Copilot/Passengers
Auxiliary Stereo Input Jack
Single Engine Driven Vacuum Pump System
Backup Mechanical Instruments

- Attitude (Vacuum Gyro)
- Airspeed
- Altimeter

Magnetic Compass
Pitot System - Heated
Static System
Alternate Static Source
Audible Stall Warning System – Heated
Deck Skin Cooling Fan #1
Avionics Cooling Fan #2 - PFD
Avionics Cooling Fan #3 – MFD
Aft Avionics Cooling Fan #4

Specification and Description

“Exhibit A”

ELECTRICAL POWER:

Alternator, 28 Volt, 95 Amp

Battery, 24 Volt, 15.5 AH, Manifold Type

Standby Battery, 24 volt 6.2 AH

Standby Battery Controller

Electrical Circuit Panel

- Ignition & Starter Switch, Key Operated
- Alternator/Battery Master Switch
- Split Avionics Master Switch
- Circuit Breakers, Electrical
- Switch Breakers, Electrical

Electrical J-Box

- Alternator Control Unit
- Battery Current Sensor
- Ground Service Receptacle
- Starter Relay
- Alternator Relay
- Battery Relay
- Ground Power Relay

Propeller De-ice Timer (turbocharged models)

Auxiliary Power Jack -12 Volt (fore & aft)

ENGINE INDICATION SYSTEM (ELECTRONIC)

Ammeter

Voltmeter

Vacuum

Manifold Pressure

Oil Pressure and Temperature

Tachometer - Hour Recorder

Fuel Flow (GPH)

LH/RH Fuel Quantity

CHT - Cylinder Head Temperature

EGT - Exhaust Gas Temperature (Normally Aspirated)

TIT - Turbine Inlet Temperature (Turbocharged)

Flight Hour Recorder

Electronic Checklists

ANNUNCIATION – CAUTION AND WARNING ALERTS (PFD)

- LH & RH Low Fuel
- Low Vacuum
- Low Oil Pressure
- Low Voltage
- Pitch Trim
- Standby Battery
- Pitch Trim
- Self Test Message Advisories
- Traffic (standard TIS)
- Propeller Heat (turbocharged models)

ENVIRONMENTAL:

Windshield Defroster, Pilot/Copilot

Ventilator, Adjustable (6 places)

Heating System, Shrouded Muffler w/Firewall Valve

Insulation / Soundproofing

Carbon Monoxide Detection System

Oxygen System

- Oxygen Bottle – 76 Cu. Ft.
- Oxygen Ports w/Masks – Pilot/Copilot/Passengers
- Oxygen Indicator – Overhead Console

EXTERIOR:

Epoxy Corrosion Proofing, All Structure

LH Door, Pilot w/Hinged Window, Lock and Key

RH Cargo Door, w/Lock and Key

Openable Window – RH (Copilot)

Rear Window

All Windows Tinted

Fixed Landing Gear

White Polyurethane Exterior Paint

Refueling Steps and Handles, Wing

Specification and Description

“Exhibit A”

Struts and Fuselage
Fixed Cabin Entrance Steps
Tie Down Rings, LH/RH Wing & Tail
Tube Type Tires

- Nose – 5.00 X 5
- Mains - 6.00 X 6

Conical Camber Wing Tip
Strut Braced, Camber Lift Wings
Static Wicks

EXTERIOR LIGHTS:

Ground Recognition - Vertical Tail,
Reduced Drag
Navigation, LH/RH Wing Tip & Tail
Navigation Light Detectors, LH/RH
Wing Tip Strobe, LH/RH
High Intensity Discharge (HID) Landing and Taxi Lights, LH Wing

- HID Electronic Ballast

Underwing Courtesy, LH/RH

FLIGHT CONTROLS:

Hydraulic Brakes, Toe-Operated
Parking Brake
Stainless Steel Control Cables
Dual Flight Controls - Aileron/Elevator/Rudder
Leather Wrap Control Wheels, All Purpose Pilot/Copilot
Pilot Control Wheel

- Pitch Trim
- AP Disconnect

Elevator Trim - Manual/Electric - KAP-140 Autopilot
Rudder Trim - Manual
Electrical Preselect - Flaps
Steerable Nose Wheel
Aileron and Elevator Lock

FUEL SYSTEM:

Electric Auxiliary Fuel Pump
Engine Driven Fuel Pump
Integral Wet Wing Fuel Tanks, 87 Gal. Usable
Fuel Selector Valve, Left/Both/Right/Off
Fuel Strainer, Incorporated with Fuselage Quick Drain
Fuel Tank Quick Drain, 5 per wing
Fuel Sampler Cup
Fuel Vapor Return System

INTERIOR:

General interior color scheme is Taupe / Charcoal
Kydex door sidepanel - decorative fabric inserts
Leather Seating Surfaces w/ Perforated Leather Insert w/ Vinyl trim
Vinyl grip flooring in crew area
Carpeting in passenger area
Cup Holders - Pilot/Copilot/Passenger
Jepp Map Storage Console w/Cup Holders
Approach Plate Holder, Pilot Control Wheel
Armrests - Pilot & Copilot Doors/Passenger Side Panels
Amsafe Inflatable Seat Belts &
Shoulder Harness STC, Inertia Reel, Pilot, Copilot, Passenger 3 & 4 Seats
Pilot and Copilot Seats

- Adjustable Fore and Aft
- Reclining Backs
- Vertical Adjustment

Rear, Passenger 3 & 4 Seats (Removable)

- Adjustable Fore and Aft
- Reclining Backs

Rear, Passenger 5 & 6 Bench Seat (Removable)

- Reclining Back

Pilot's Check List

Specification and Description

“Exhibit A”

Pilot's Operating Handbook
Fire Extinguisher, Hand Held
Instrument Panel Glareshield
Control Wheel Lock
Clothes Hanger Bar
Metal Instrument Panel, w/Removable Stby Instr. Subpanel
Map/Glove Compartment
Baggage Net
Radio Call Plate
Map & Storage Pockets
Cabin Door Scuff Plates
Rosen Sun Visors, Pilot & Copilot
Tow Bar

INTERIOR LIGHTING:

LED Pilot/Copilot Cabin Overhead LED Lights
LED Passenger Overhead Lights
Interior Lights Dimming Control
Map Light, Pilot Control Wheel
Sub-Panel Lighting (LED Backlighting)

- Flaps
- Throttle
- Mixture
- Propeller
- Environmental Controls (Air and Heat)

Switch Panel Lighting (LED Backlighting)

- Avionics and Master Switches
- Dimming Reostats
- Landing, Taxi and Nav Switches
- Standby Battery Switch

LCD Lighted Glass Panel Displays:

- Electronic Flight Instruments
- Electronic Avionics Instruments
- Electronic Engine Instruments

Audio Panel (Backlighting)

LED Lighted Switch Panel
Radio Call Plate (Backlighting)
LED Lighted Circuit Breaker Panel
Compass Internally Lighted

POWER PLANT AND ACCESSORIES:

Lycoming TIO-540-AJ1A Engine
310 HP @2500 RPM
Certified for 100LL & 100 Fuel
Turbocharging System (Fully Automatic)

- Turbocharger, Sloped Absolute Pressure Controller
- Exhaust Wastegate Valve, Overboost Valve
- Turbocharged Exhaust w/Heater Muff
- Turbine Access Door

Fuel Injection System
Tubular Steel Engine Mount
Bed Dynafocal Engine Mounting System
Automatic Alternate Engine Air
Oil Cooler
Rigid - Shock Mounted Cowling
Manual Cowl Flaps
Induction Air Filter
Full Flow Oil Filter
Throttle Control
Vernier Mixture Control
Vernier Propeller Control
Dual Ignition System, Shielded Magneto
Engine Exhaust Muffler
McCauley Constant Speed,
3 Blade Metal Propeller w/De-ice Boots
Propeller Governor
Propeller Spinner, Polished
Electric Starter

Specification and Description

“Exhibit A”

Optional Equipment

Air Conditioning
Keith Products (STC -16,000 btuh / Engine Driven)

TAWS-B Terrain (Garmin) NAV III Avionics

TAS Traffic (Bendix King KTA 870) – NAV III Avionics

ADF KR87 – NAV III Avionics – Separate control head - displayed on PFD (Int'l only)

DME KN63 – NAV III Avionics – Integrated control - displayed on PFD (Int'l only)

Floatplane Provision Kit (Exchange Items: Hoisting Rings, Windshield V-brace and Fuselage Reinforcements)

Oversized Tires and Wheel Fairings (Exchange: Main 8.00 x 6. Nose 6.00 x 5)

Cargo Pod (16.0 Cu. Ft. of Additional Cargo Space With Loading Up to 300 lbs)

Abrasion Boots (Horizontal Stabilizer)

Exterior Striping Options

518G: Skyline Steel, Dusk Grey Metallic and Ward Red Painted Stripes; Cessna and Stationair Logo: White Vinyl; Registration Number: Burgundy Vinyl

518H: Squadron Blue, Medium Silver Metallic and Balboa Blue Painted Stripes; Cessna and Stationair Logo: White Vinyl; Registration Number: Dark Blue Vinyl

518J: Strawberry Pearl, Fawn Metallic and Gloss Black Painted Stripes; Cessna and Stationair Logo: White Vinyl; Registration Number: Black Vinyl

Interior Options

Fabric Seat Surfaces w/ Vinyl trim

Utility Interior Kit:
Vinyl Grip Flooring,
Kydex door sidepanel, vinyl inserts

Specification and Description

“Exhibit A”

Performance Conditions

All estimated performance data are based on airplane weights at 3,100 pounds; standard atmospheric conditions; level, hard surface, dry runways; and no wind. They are calculated values derived from flight tests conducted by Cessna Aircraft Company under carefully documented conditions and will vary with individual airplanes, pilots, and numerous other factors affecting flight performance.

Speed, CAS

Maximum at 17,000 ft..... 178 kts

Cruise, 75% power at 20,000 ft..... 164 kts

Cruise, 75% power at 10,000 ft..... 150 kts

Cruise (Recommended lean mixture with fuel allowance for engine start, taxi, takeoff, climb and 45-minute reserve)

75% power at 20,000 ft..... range 559 nm (1,035 km)

87 gallons usable fuel..... time 3.6 hr

75% power at 10,000 ft..... range 533 nm (987 km)

87 gallons usable fuel..... time 3.6 hr

45% power at 10,000 ft..... range 703 nm (1302 km)

87 gallons usable fuel..... time 6.3 hr

Rate of Climb at Sea Level..... 1,050 fpm (320mpm)

Service Ceiling..... 27,000 ft (8,230 m)

Takeoff Performance

· Ground roll..... 910 ft (277 m)

· Total distance over 50-ft obstacle..... 1,740 ft (530 m)

Landing Performance

· Ground roll..... 735 ft (224 m)

· Total distance over 50-ft obstacle..... 1,395 ft (425 m)

Stall Speed, CAS

· Flaps up, power off..... 62 kts

· Flaps down, power off..... 54 kts

Wing Loading..... 20.7 lbs/sq ft (101.1 kg/sq m)

Power Loading..... 11.6 lbs/hp (5.27 kg/hp)

Engine: Lycoming - TIO-540-AJ1A 310 BHP @2,500 RPM

Propeller: McCauley 3-bladed Constant Speed, Diameter 79 in (2.01 m)

Specifications subject to change without notice.

Specification and Description

“Exhibit A”

CESSNA'S LIMITED WARRANTY (SINGLE ENGINE PISTON AIRCRAFT)

Cessna warrants the aircraft and all parts included therein to be free from defects in material and workmanship under normal use and service for a period of twenty-four (24) months after delivery to the original retail purchaser or first user, except as hereafter noted. Cessna's limited warranty also applies to aircraft paint; however, the warranty period for aircraft paint is twelve months after delivery of the aircraft to the original retail purchaser or first user. Engines, engine part accessories, avionics, batteries and propellers, are specifically excluded from this warranty.

Replacement spare parts sold by Cessna, excluding engines, engine part accessories, avionics, batteries and propellers are warranted for 6 months after installation or first use, except as hereafter noted. Cessna's obligation under this warranty is limited to repairing or replacing, at its option, with exchange, overhauled, or new parts, found defective by its examination which are returned by the owner within the applicable twenty-four (24) or six (6) month period to any Cessna appointed or Cessna Contracted Distributor appointed Service Station. Replacement parts are warranted only for the remainder of the applicable twenty-four (24) or six (6) month original warranty period. The repair or replacement of defective parts under this warranty will be made without charge to the owner for parts and labor for removal, installation and/or actual repair, except that the owner shall pay all import duties, sales and use taxes on replacements.

This limited warranty does not apply to parts subjected to misuse, negligence, improper installation, accident, alteration; repairs not authorized by Cessna; normal

maintenance services (cleaning, control rigging, brake and other mechanical adjustments, maintenance inspections, etc.); replacement of service items (light bulbs, brake linings, filters, hoses, tires, cowl mounts, etc.); or to normal deterioration of soft trim and appearance items (paint, upholstery, rubber-like items, etc.) due to wear and exposure.

TO THE EXTENT ALLOWED BY APPLICABLE LAW, THIS LIMITED WARRANTY IS EXPRESSLY IN LIEU OF AND CESSNA SPECIFICALLY DISCLAIMS AND EXCLUDES ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED IN FACT OR BY LAW, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES OF REPAIR OR REPLACEMENT ARE THE ONLY REMEDIES UNDER THIS WARRANTY. CESSNA DISCLAIMS AND EXCLUDES ALL OTHER OBLIGATIONS AND LIABILITIES WHETHER IN CONTRACT OR IN TORT, INCLUDING LOSS OF USE, LOSS OF TIME, LOSS OF VALUE, INCONVENIENCE, COMMERCIAL LOSS OR ANY OTHER DIRECT, CONSEQUENTIAL, SPECIAL OR INCIDENTAL DAMAGES.

Specification and Description

“Exhibit A”

Textron Lycoming Warranty (Limited) New Reciprocating Aircraft Engine

What Textron Lycoming Promises You

Engine Model Aircraft Model

IO-360-L2A Cessna-172R, 172S

IO-540-AB1A5 Cessna-182T

IO-540-AC1A5 Cessna-206H

TIO-540-AK1A Cessna-T182T

TIO-540-AJ1A Cessna-T206H

Textron Lycoming warrants the above listed new reciprocating engine models sold by it to be free from defects in material and workmanship for a period of twenty-four (24) months after aircraft delivery to the original retail purchaser or first user.

The date of first operation must not exceed two (2) years from the date of shipment from Textron Lycoming.

Textron Lycoming's obligation under this warranty shall be limited to its choice of repair or replacement, on an exchange basis, of the engine or any part of the engine, when Textron Lycoming has determined that the engine is defective in material or workmanship. Such repair or replacement will be made by Textron Lycoming at no charge to you. Textron Lycoming will also bear the cost for labor in connection with the repair or replacement as provided in Textron Lycoming's then current Removal and Installation Labor Allowance Guidebook.

Any engine or part so repaired or replaced will be entitled to warranty for the remainder of the original warranty period.

YOUR OBLIGATIONS

The engine must have received normal use and service. You must apply for warranty with an authorized Textron Lycoming

distributor within 30 days of the appearance of the defect in material or workmanship.

Textron Lycoming's warranty does not cover normal maintenance expenses or consumable items, the obligations on the part of Textron Lycoming set forth above are your exclusive remedy and the exclusive liability of Textron Lycoming. This warranty allocates the risk of product failure between you and Textron Lycoming, as permitted by applicable law.

Textron Lycoming reserves the right to deny any warranty claim if it reasonably determines that the engine or part has been subject to accident or used, adjusted, altered, handled, maintained, or stored other than as directed in your operator's manual, or if non-genuine Textron Lycoming parts are installed in or on the engine and are determined to be a possible cause of the incident for which the warranty application is filed.

Textron Lycoming may change the construction of engines at any time without incurring any obligation to incorporate such alterations in engines or parts previously sold.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS OR IMPLIED OR STATUTORY, WHETHER WRITTEN OR ORAL, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTY ARISING FROM ANY COURSE OF PERFORMANCE OR DEALING OR TRADE USAGE. THIS WARRANTY IS ALSO IN LIEU OF ANY OTHER OBLIGATION, LIABILITY, RIGHT, OR CLAIM, WHETHER IN CONTRACT OR IN TORT, INCLUDING ANY RIGHT IN

Specification and Description

“Exhibit A”

STRICT LIABILITY IN TORT OR ANY RIGHT ARISING FROM NEGLIGENCE ON THE PART OF TEXTRON LYCOMING, AND TEXTRON LYCOMING'S LIABILITY ON SUCH CLAIM SHALL IN NO CASE EXCEED THE PRICE ALLOCABLE TO THE ENGINE OR PART WHICH GIVES RISE TO THE CLAIM.

**LIMITATION OF LIABILITY
IN NO EVENT, WHETHER AS A RESULT OF A BREACH OF WARRANTY, CONTRACT, OR ALLEGED NEGLIGENCE, SHALL TEXTRON LYCOMING BE LIABLE FOR SPECIAL OR CONSEQUENTIAL OR ANY OTHER DAMAGES, INCLUDING BUT NOT LIMITED TO LOSS OF PROFITS OR REVENUES, LOSS OF USE OF THE ENGINE, OR COST OF A REPLACEMENT.**

No agreement varying this warranty or Textron Lycoming's obligations under it will be binding upon Textron Lycoming unless in writing signed by a duly authorized representative of Textron Lycoming.

**Cessna Model Aircraft Only
Textron Lycoming Engines
652 Oliver Street
Williamsport, Pennsylvania 17701
(570) 323-6181
www.lycoming.textron.com
Original Engine Installation Only
Effective 2000**

McCauley Propeller Systems Standard Limited Warranty

McCauley Propeller Systems, a Division of Cessna Aircraft Company, Wichita, Kansas, U.S.A., expressly warrants new and remanufactured products produced and sold by McCauley to be free from defects in material and workmanship under normal use and service for a period of thirty-six (36) months after delivery to the original retail purchaser or until the expiration of the maximum hours of use or calendar limits for overhaul published by McCauley for the subject product, whichever occurs first.

McCauley's obligation under this limited warranty is limited to repairing or replacing, at its sole option, any propeller, propeller parts, governor or governor parts determined by McCauley to have been defective and which are properly returned by the owner, with a written statement describing the alleged defect, to any McCauley Authorized Service Center authorized to service the individual McCauley product. The repair or replacement of defective parts will be made without charge to the owner for parts, or labor for removal and installation, except export/import duties, and/or sales or use taxes, if any which are solely the owner's responsibility. McCauley will warrant a part replaced pursuant to this limited warranty under the same terms as the original part for the remainder of the applicable warranty period of the original part. This limited warranty is not intended to and does not cover the costs of normal maintenance of overhaul.

In addition, McCauley will repair or replace, at its option, any propeller, propeller parts, governor, or governor parts requiring replacement due to manufacturing defect if found at or before the first recommended overhaul interval as described in

Specification and Description

“Exhibit A”

McCauley published service information. This first overhaul coverage does not include labor, standard overhaul replacement parts, parts repairable via published service information (re-plating, painting, etc.), other costs associated with the propeller or governor overhaul, or export/import duties, and/or sales or use taxes, nor does it apply to defects found after McCauley published overhaul hour or calendar limits. The provisions of this limited warranty do not apply to: any McCauley parts which have been subject to misuse, negligence or accident or which have been repaired or altered in any way that, in the sole judgment of McCauley, adversely affects their performance, stability or reliability; to normal maintenance services (such as cleaning, mechanical adjustments and maintenance inspections); to the replacement of service items made in connection with normal maintenance; to normal deterioration of soft trim and appearance items (such as paint and rubber-like items) due to wear and exposure; to propellers, governors or parts found defective beyond the McCauley recommended overhaul period; or to parts which have been improperly installed by entities other than McCauley and/or McCauley Authorized Service Centers.

The McCauley limited warranty is void on any new or remanufactured product installed, without McCauley's prior written approval, on a non-type certificated engine, or on any engine which has received an overhaul or modification which is not approved by the engine manufacturer and that results in a change to the vibratory environment of the engine such as, but not limited to, an alteration of horsepower, operating RPM, crankshaft damper configuration, compression ratio, magneto timing, camshaft design, or any other overhaul or modification not expressly approved by the original engine manufacturer. The McCauley limited warranty is also void on any McCauley product shipped new from the factory or distributor in

dis-assembled state, then later re-assembled by an unauthorized party. Parties authorized to re-assemble factory-new product must have specific written permission from McCauley to do so, otherwise all McCauley warranty on the affected unit is void. No McCauley warranty coverage is offered for leakage on product assembled outside McCauley, regardless of the assembling party.

To the extent allowed by applicable law, **THIS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED IN FACT OR BY LAW, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES OF REPAIR OR REPLACEMENT SET FORTH HEREIN ARE THE ONLY REMEDIES UNDER THIS LIMITED WARRANTY. McCAULEY DISCLAIMS ANY OBLIGATION OR LIABILITY, WHETHER IN CONTRACT OR IN TORT , INCLUDING LOSS OF USE OF THE PRODUCT WARRANTED, LOSS OF TIME, INCONVENIENCE, LOSS OF PROFITS, COMMERCIAL LOSS, OR ANY OTHER DIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES. THIS WARRANTY IS IN LIEU OF ANY OBLIGATION OR LIABILITY ON THE PART OF McCAULEY TO ANYONE OF ANY NATURE WHATSOEVER BY REASON OF THE MANUFACTURE, SALE, LEASE, OR USE OF THE WARRANTED PRODUCTS AND McCAULEY NEITHER ASSUMES NOR AUTHORIZES ANYONE TO ASSUME FOR IT ANY OTHER OBLIGATION OR LIABILITY IN CONNECTION WITH SUCH WARRANTED PRODUCTS. THE UNITED NATIONS CONVENTION ON CONTRACTS FOR THE INTERNATIONAL SALE OF GOODS, 1980, AND ANY SUCCESSOR THERETO, IS EXPRESSLY EXCLUDED FROM THIS WARRANTY.**
Issued 9/1/2003

Specification and Description

“Exhibit A”

Bendix/King Equipment Retail Warranty Statement For Cessna Aircraft Company Single Engine Program

A. General Aviation Avionics products manufactured by Honeywell under the brand name Bendix/King (collectively referred to herein as "Honeywell") are warranted against defects in design, material, or workmanship caused by Honeywell or its authorized agent(s) for the warranty period as defined in Paragraph (B) of this statement, which occur under normal and intended use and service, subject to all of the qualifications and conditions hereinafter stated.

B. The warranty term for new product(s) installed on new aircraft shall be twenty-four (24) months from delivery to the original retail purchaser or first user. Cessna to provide warranty start date information. C. Any product Honeywell finds to be in violation of the warranty as set out in Paragraph (A) hereof, at the option of Honeywell, shall be repaired, replaced, or exchanged in accordance with the following procedures:

1. Products shall be returned to any authorized Honeywell Service Center or Honeywell Regional Product Support Repair/Overhaul Facility, with transport charges prepaid.
2. After correction, the products shall be returned to the purchaser with surface transportation charges prepaid.
3. The risk of loss or damage to all products in transit shall be borne by the party initiating the transportation of such products unless the purchaser makes a request for specific mode of transportation. In such case, the risk of loss and the cost of shipment shall be borne by the purchaser. All items repaired or replaced hereunder shall be warranted for the unexpired portion of the original warranty period. D. This warranty specifically

excludes defects that Honeywell determines to be the result of any or all of the following:

1. Abuse, accident, or misuse;
2. Contamination, negligence, tampering, or improper storage or maintenance;
3. Repair or attempted repair by unauthorized persons or use of non-Honeywell or unauthorized repair or replacement parts;
4. Products not installed by an authorized Honeywell Installation Facility in accordance with the appropriate installation manual.

E. The warranty as set out in Paragraph (A) is the only warranty for Honeywell products and is in lieu of all other warranties expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose that are herewith expressly excluded and disclaimed.

F. The remedies as set out in Paragraph (C) hereof state the entire liability of Honeywell and constitute the sole and exclusive remedy of the purchaser. Honeywell shall not be liable for any other claim, loss, or damage, including, but not limited to, incidental, consequential, or other kinds of damages whether based on contract, tort, negligence, or other theory of product liability.

G. Honeywell reserves the right to make design changes, additions to, and improvements in its products without the obligation to install same in products previously manufactured.

THIS IS A LIMITED WARRANTY

Honeywell

23500 W. 105th Street

Olathe, Kansas 66061

Specification and Description

“Exhibit A”

Garmin Avionics Installed in Single Engine Aircraft

Aircraft OEM-Installed Avionics 2-Year Limited Warranty Policy

This GARMIN Product is warranted to be free from defects in materials or workmanship for two years from the date of warranty activation. Within this period, GARMIN International, Inc. will at its sole option, repair or replace any components which fail in normal use. Such repairs or replacement will be made at no charge to the customer for parts or labor, provided that the customer shall be responsible for any transportation cost. This warranty does not cover failures due to abuse, misuse, accident or unauthorized alteration or repairs.

THE WARRANTIES AND REMEDIES CONTAINED HEREIN ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED OR STATUTORY, INCLUDING ANY LIABILITY ARISING UNDER ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, STATUTORY OR OTHERWISE. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, WHICH MAY VARY FROM STATE TO STATE.

IN NO EVENT SHALL GARMIN BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, WHETHER RESULTING FROM THE USE, MISUSE OR INABILITY TO USE THIS PRODUCT OR FROM DEFECTS IN THE PRODUCT. Some states do not allow the exclusion of incidental or consequential damages, so the above limitations may not apply to you.

GARMIN retains the exclusive right to repair or replace the product or offer a full refund of the purchase price at its sole discretion. **SUCH REMEDY SHALL BE YOUR SOLE AND EXCLUSIVE REMEDY FOR ANY BREACH OF WARRANTY.**

To obtain warranty service, contact your local GARMIN authorized Service Center. For assistance in locating a Service Center near you, call GARMIN Customer Service at one of the numbers shown below.

**GARMIN International
1200 East 151st Street
Olathe, Kansas 66062, U.S.A.
Toll free: 1-800-800-1020
Phone: 1-913-397-8200
FAX: 1-913-397-0836**

**GARMIN (Europe) Ltd.
Unit 5, The Quadrangle
Abbey Park Industrial Estate
Romsey, SO51 9AQ, U.K.
Phone: 44-1794-519944
FAX: 44-1794-519222
Visit our web site at: www.garmin.com**